

## Eaton Industrial Hose EH081 - STEAM SLAYER™ YELLOW / RED



# Overview & Features

Transfer of steam for processing products and cleaning services

### Features

- -40 F to 407 F ( 450 F for superheated steam)
- 2 wire braid steel reinforcement
- 250 psi operating pressure
- 10:1 safety factor
- Cover: EPDM
- Tube: Chlorobutyl
- EH080 – Black
- EH084 – Black / Red (Barber Pole)

# Where Used



### Aerospace

**Applications:**

- Steam Transfer



### Buildings

**Applications:**

- Steam Transfer



### Food and beverage

**Platforms:**

- In-Plant Processing

**Applications:**

- Steam Transfer



### Government

**Applications:**

- Steam Transfer



### Machine building

**Applications:**

- Steam Transfer



### Marine

**Applications:**

- Steam Transfer



### Mining, metals and minerals

**Platforms:**

- Ball Mill
- Coal Mill
- Foundry Casting
- Steel Mill Furnaces

**Applications:**

- Steam Transfer



### Oil and gas

**Platforms:**

- Downstream: Petrochemical
- Downstream: Refining (Ethanol/ Biodiesel)
- Downstream: Terminal Operations (refined gas and liquids)
- Midstream: Saddle Plants
- Midstream: Terminal Operations (unrefined gas and liquids)
- Pipeline
- Upstream: Offshore (fixed or floater) Offloading Systems
- Upstream: Onshore Drilling Operations

**Applications:**

- Steam Transfer



### Pharmaceuticals

**Applications:**

- Steam Transfer



### Rail

**Applications:**

- Steam Transfer



### Renewables

**Platforms:**

- Dry Steam
- Flash Steam

**Applications:**

- Steam Transfer

 **Water and wastewater**

- Applications:**
- Steam Transfer

# Value Propositions

---

★ = Denotes point of differentiation

Value Proposition Statement	Audiences		
	OEM	Distributor	End User
Completes breadth of portfolio to capitalize on core product market opportunities			
Easy identification in the toughest environments provided by dual Mylar and embossed laylines , verses competitive single layline alternatives, creating ease of replenishment and traceability			
Leverage increased service life, higher level of safety and up-time on critical steam applications			
★ Steam slayer has surpassed 2000 hours in saturated steam test without failure, significantly outlasting the competition			
★ Chlorobutyl tube is more heat and failure resistant than standard EPDM inner tube compounds			

# Tools & Collateral

---

## Brochure

[Eaton Steam Slayer EH084](#)

## Catalog

[Industrial Hose Catalog North America : E-HOOV-MC003-E2](#)

[Industrial Hose Oil and Gas Exploration](#)

## Press Releases

[Eaton Steam Slayer](#)