

## Eaton Industrial Hose H9568 - CONCORD 250™ STEAM



# Overview & Features

Transfer of steam for processing products and cleaning services

### Features

- 250 psi operating pressure
- 450 F
- Cover: EPDM
- 2 wire braid steel reinforcement
- Tube: EPDM
- 10:1 safety factor

# Where Used



### Aerospace

**Applications:**

- Steam Transfer



### Buildings

**Applications:**

- Steam Transfer



### Food and beverage

**Platforms:**

- In-Plant Processing

**Applications:**

- Steam Transfer



### Government

**Applications:**

- Steam Transfer



### Machine building

**Applications:**

- Steam Transfer



### Marine

**Applications:**

- Steam Transfer



### Mining, metals and minerals

**Platforms:**

- Ball Mill
- Coal Mill
- Foundry Casting
- Steel Mill Furnaces

**Applications:**

- Steam Transfer



### Oil and gas

**Platforms:**

- Downstream: Petrochemical
- Downstream: Refining (Ethanol/ Biodiesel)
- Downstream: Terminal Operations (refined gas and liquids)
- Midstream: Saddle Plants
- Midstream: Terminal Operations (unrefined gas and liquids)
- Pipeline
- Upstream: Offshore (fixed or floater) Offloading Systems
- Upstream: Onshore Drilling Operations

**Applications:**

- Steam Transfer



### Pharmaceuticals

**Applications:**

- Steam Transfer



### Rail

**Applications:**

- Steam Transfer



### Renewables

**Platforms:**

- Dry Steam
- Flash Steam


**Applications:**

- Steam Transfer



### Utilities

**Applications:**



Applications:

- Steam Transfer

# Value Propositions

★ = Denotes point of differentiation

Value Proposition Statement	Audiences		
	OEM	Distributor	End User
Completes breadth of portfolio to capitalize on core product market opportunities			

# Tools & Collateral

Brochure

- [Eaton Concord 250 Steam H9568](#)
- [Industrial Hose Oil and Gas Exploration](#)

Catalog

- [Industrial Hose Catalog North America : E-HOOV-MC003-E2](#)